



Manufacturer reserves the right to modify, without notice, specific designs and specifications as deemed advisable on the trailer described herein without obligation in regards to trailers previously sold. Written warranty covers each trailer. No other warranty expressed or implied is made. Warranty on tires and brakes through original manufacturer. All dimensions are approximate. Some equipment shown may be optional. See your Big Tow Trailers dealer for details.

Specifications	BE-5BL	BE-6BL
WEIGHT (lbs/kg)	3,260 or 3,460 / 1479 or 1569	3,360 or 3,560 / 1524 or 1615
CAPACITY (lbs/kg)	10,000 / 4536 with adequate hitch load	12,000 / 5443 with adequate hitch load
DECK LENGTH (ft-in/mm)	14'-0" or 16'-0" / 4267 or 4877 with 3'-0" beavertail @ 9 deg.	14'-0" or 16'-0" / 4267 or 4877 with 3'-0" beavertail @ 9 deg.
DECK HEIGHT (ft-in/mm)	21.5" / 546 empty	22.5" / 572 unloaded
OVER-ALL WIDTH (ft-in/mm)	8'-6" / 2591	8'-6" / 2591
LOAD WIDTH (in/mm)	82" / 2083 between fenders	82" / 2083 between fenders
TONGUE LENGTH (ft-in/mm)	5'-0" / 1524	5'-0" / 1524
RAMPS (ft-in/mm)	Auto-Latch™, adj., 4'-0" / 1219 long., 15-deg. cleat style	Auto-Latch™, adj. 4'-0" / 1219 long., 15-deg. cleat style
DECK TYPE	2" nominal white oak screwed down (flush deck)	2" nominal white oak screwed down (flush deck)
BRAKES	Electric, with break-away, 12"x2"	Electric, with break-away, 12"x2"
TIRES	(4) ST225/75R x 15, load range D	(4) 235/85R x 16, load range E
WHEELS	(4) 6" x 15" white modular, 6-bolt on 5.5" b.c.	(4) 6" x 16" white modular, 6-bolt on 5.5" b.c.
AXLES	(2) 6,000 lb. Torflex	(2) 6,000 lb. Torflex
AXLE LOCATION	11'-8" or 13'-2" from front of deck to center of axles	11'-8" or 13'-2" from front of deck to center of axles
HITCH	Adjustable, 2-5/16" ball coupler or 3" I.D. pintle ring	Adjustable, 2-5/16" ball coupler or 3" I.D. pintle ring
TIE DOWNS	(6) stake pockets (3 per side)	(6) stake pockets (3 per side)
PARKING JACK	Single 7K drop-leg (bolted on)	Single 7K drop-leg (bolted on)
SAFETY CHAINS	(2) 3/8" high tensile x 40" with safety latch hooks	(2) 3/8" high tensile x 40" with safety latch hooks
TOOL BOX	Standard, (Lid optional)	Standard, (Lid optional)
MUD FLAPS	Standard	Standard
SIDE RAILS	5" high	5" high
MAIN FRAME	High tensile W6 x 12 beam (one piece cold-formed tongue/frame)	High tensile W6 x 12 beam (one piece cold-formed tongue/frame)
HEAD BOARD	5" high, channel iron	5" high, channel iron
X-MEMBERS	3" channel iron	3" channel iron
WIRING	Sealed modular harness	Sealed modular harness
LIGHTING (reflectorized)	Sealed beam, flush/shock mounted	Sealed beam, flush/shock mounted
REG. HOLDER	Standard	Standard
FINISH (before decking)	5-stage polyurethane under and overcoat system	5-stage polyurethane under and overcoat system
	<ul style="list-style-type: none"> ▪ Hydraulic surge brakes w/freebacking (check D.O.T. laws) ▪ EZ Lube hubs ▪ Spring assist ramps ▪ Lockable tool box lid ▪ Fork holders 	<ul style="list-style-type: none"> ▪ Hydraulic surge brakes w/freebacking (check D.O.T. laws) ▪ EZ Lube hubs ▪ Spring assist ramps ▪ Lockable tool box lid ▪ Fork holders