



**Chicago  
Pneumatic**



**CPG 20/25**

**High performance products.  
Designed for you!**

# Technical Data

## Model

## CPG 20/25

|   |             |
|---|-------------|
| Sound Pressure Level @ 23 feet @ 75% load | 65 dB(A)    |
| Fuel Tank Capacity                        | 30 gal.     |
| Fuel Consumption At 75% Load              | 1.04 gal/hr |
| Fuel Autonomy At 75% Load                 | 29 hr       |

## Engine

## Kubota

|                     |                    |
|---------------------|--------------------|
| Model               | V2403              |
| Rated Speed         | 1800 rpm           |
| Emission Compliance | EPA IT4            |
| Rated Output        | 29.6 HP @ 1800 rpm |
| Coolant             | Water / Glycol     |
| Cylinders           | 4                  |
| Displacement        | 2.4 L              |
| Engine Control      | Electronic         |

## Alternator

## Leroy Somer

|   |          |
|---|----------|
| Model                                   | LSA40M5  |
| Degree Of Protection / Insulation Class | IP23 / H |

## Dimensions

|                                  |                     |
|----------------------------------|---------------------|
| Dimensions Skid (L x W x H)      | 70 x 33.5 x 46.4 in |
| Weight - Skid Wet                | 1,868 lbs           |
| Dimensions w/Trailer (L x W x H) | 110 x 59 x 57 in    |
| Weight - w/Trailer Wet           | 2,121 lbs           |

## Convenience Receptacles

|                                    |   |
|------------------------------------|---|
| 20 amp - 125 volt GFCI duplex      | 2 |
| 50 amp - 125 / 250 volt twist lock | 2 |

## CPG 20

|                                  |                    |
|----------------------------------|--------------------|
| Rated Standby Power              | 19.2 kW / 19.2 kVA |
| Rated Prime Power                | 17.3 Kw / 17.3 kVA |
| Voltage Selections - 1Ø          | 120 / 240          |
| Amperage Capacity @ 120 volts 1Ø | 2 x 66 amps        |
| Amperage Capacity @ 240 volts 1Ø | 70 amps            |

## CPG 25

|                                  |                |
|----------------------------------|----------------|
| Rated Standby Power              | 22 kW / 22 kVA |
| Rated Prime Power                | 20 Kw / 25 kVA |
| Voltage Selections - 3Ø          | 208/240/480    |
| Amperage Capacity @ 208 volts 3Ø | 69             |
| Amperage Capacity @ 240 volts 3Ø | 60             |
| Amperage Capacity @ 480 volts 3Ø | 30             |

## Standard Features

- Reliable Kubota engine and Leroy Somer alternator
- 29 hour run time at 75% load with integrated 30 gallon in-frame fuel tank
- Environmentally friendly 110% fluid containment frame
- Solid-state digital controller with easy-to-read analog gauges
- Very quiet 65 dB(A)
- Electronic governor for increased voltage stability (0.25%)
- 3 position voltage selector switch (CPG 25 only)
- Remote start connections

## Options

- Skid-mounted
- Battery charger
- Coolant heater
- Spare tire
- Tool box
- Rear stabilizer jacks
- External fuel connections

Since 1901 the Chicago Pneumatic name has represented high performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, accessories and workshop equipment, please visit [www.cp.com](http://www.cp.com) or call (800) 760-4049.

