



CPG 70

High performance products.

Designed for you!

Technical Data

CPG 70
62 kW / 78 kVA
56 Kw / 70 kVA
208/240/480
120/240
2 x 180 amps
180 amps
195
168
84
oad 67 dB(A)
170 gal.
3.4 gl/hr
49.2 hr

Engine	John Deere
Model	4045TF285
Rated Speed	1800 rpm
Emission Compliance	EPA Tier III
Rated Output	99 HP @ 1800 rpm
Coolant	Water / Glycol
Cylinders	4
Displacement	4.5 L
Engine Control	Electronic

Alternator	Stamford
Model	UCI 224 E
Degree Of Protection / Insulation Class	IP23 / H



Dimensions

Dimensions Skid (L x W x H)	112 x 44 x 67 in
Weight - Skid Wet	5,310 lbs
Dimensions w/Trailer (L x W x H)	176 x 78 x 80 in
Weight - w/Trailer Wet	6,560 lbs

Convenience Receptacles

2 x 20 amp - 125 volt GFCI duplex	2
2 x 50 amp - 125 / 250 volt twist lock	2

Standard Features

- Reliable John Deere engine and Stamford alternator
- 49.2 hour run time at 75% load with integrated 170 gallon in-frame fuel tank
- Environmentally friendly 110% fluid containment frame
- Solid-state digital controller with easy-to-read analog gauges
- Very quiet 67 dB(A)
- Electronic governor for increased voltage stability (0.25%)
- · Remote start connections

Options

- Skid-mounted
- · Battery charger
- Coolant heater
- · Spare tire
- Tool box
- Rear stabilizer jacks
- External fuel connections

Since 1901 the Chicago Pneumatic name has represented high performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, accessories and workshop equipment, please visit www.cp.com or call (800) 760-4049.